



(19)

Generated Document

(11) Publication number: **05168144 A**

PATENT ABSTRACTS OF JAPAN

(21) Application number: **03351095**

(51) Int. Cl.: H02H 7/00 H02H 3/20 H02M 1/00 H02M 3/28

(22) Application date: **11.12.91**

(30) Priority:		(71) Applicant: MURATA MFG CO LTD
(43) Date of application publication:	02.07.93	(72) Inventor: NAGATSUMA TSUKASA NAKAHIRA KOJI
(84) Designated contracting states:		(74) Representative:

(54) SWITCHING POWER SUPPLY

(57) Abstract:

PURPOSE: To protect a switching element against breakdown due to heating by providing a resistor connected in series with the switching element, a capacitor, a switch circuit, and a protective control circuit.

CONSTITUTION: When a current ID flowing through a switching

element 4 exceeds a predetermined level, voltage V3 across a resistor 26 connected in series with the switching element 4 also exceeds a predetermined level and thereby a switch circuit 30 is turned ON to start charging of a capacitor 28. When the current ID flowing through the switching element 4 is sustained above the predetermined level, charging operation of the capacitor 28 is sustained and when the voltage V4 across the capacitor 28 exceeds a predetermined level, switching operation of the switching element 4 is forcibly stopped through a protective control circuit 40. Consequently, the switching element 4 is protected against thermal breakdown at the time of overload.

COPYRIGHT: (C)1993, JPO&Japio



